

Sealed combustion chamber gas fired storage water heater

SECURITY SX160



Product details



ErP Ready



Low Emissions

Methane

Code **SX160**

Price € **3.310,00**


Propane

Code **SX160P**

Price € **3.330,00**



Kit di scarico da pag. 44





Device operating with ATI original flue kits only

Main characteristics

- Internal glazing
- Closed-cell polyurethane foam insulation
- Electronic ignition
- Corrosion protection with magnesium anode
- Adjustable thermostat and overheat safety thermostat
- Stainless steel multigas burner, natural gas or propane ready
- Flue safety pressure switch
- Overpressure safety valve
- Inspection and cleaning flange
- Various ATI flue kits available

Technical data		
Storage capacity	L	160
Nominal input (gross)	kW	13,00
Nominal output (net)	kW	11,96
Warm up time ($\Delta T= 45^{\circ}\text{C}$) .	min	42
Continuous water at 40°C	l/h	411
Draw-off capacity single withdrawal*	L	320
Methane consumption (G20)**	m ³ /h	1,40
Propane consumption (G31)**	kg/h	1,00
Max operating pressure	bar	6
Net weight	kg	120
Connections		
Cold Water Inlet	F	G 3/4"
Hot Water Outlet	C	G 3/4"
Recirculation	R	G 3/4"
Gas Inlet	G	G 1/2"
Exhaust fumes - concentric	S	$\varnothing 60/100, \varnothing 80/125$
Exhaust fumes - split		$\varnothing 80 \varnothing 80$
Packaging		
Packages	n.	2
Wooden cage (l x w x h) - (weight)	cm - (kg)	58x58x185 - (132)
Box (l x w x h) - (weight)	cm - (kg)	46x46x23 - (6)



*Under standard conditions: T in 15°C , T out 40°C , T storage 65°C

**Under standard conditions: T in 15°C , 1013 mbar